

# MIT515, MIT525, MIT1025, MIT1525

## 5 kV, 10kV, 15 kV DC Insulation Resistance Testers



- **30 TΩ maximum resistance**
- **PI, DAR, DD, SV and ramp test**
- **Operate from battery or AC source**
- **Rapid charge Li-ion battery**
- **Safety rated CATIV 1000 V to 3000 m (15 kV)**
- **Advanced memory with time/date stamp**

### DESCRIPTION

Megger's new range of DC insulation testers MIT515, MIT525, MIT1025 and MIT1525 are targeted at original equipment manufacturers and industrial companies. The top of the range MIT1525 performs insulation resistance tests up to 15 kV with a 30 TΩ maximum resistance and an accuracy of  $\pm 5\%$  from 1 MΩ up to 3 TΩ. The MIT515 offers IR, DAR and PI functions but has no memory functionality. MIT525, MIT1025 and MIT1525 have a full suite of test modes as well as on-board memory and the ability to stream data/download data to a PC/laptop.

Instrument productivity is a focus of the new MIT range which offers rapid charge batteries and operation from an AC source if the batteries are flat. Rapid charge batteries enable > 60 minutes testing after a 30 minute charge.

Safety rating is not compromised on the MIT range with all terminals safety rated to CATIV 600 V to 3000 m (5 kV, 10 kV or CATIV 1000 V to 3000 m (15 kV). A range of 5 kV and 10 kV test leads are available plus dedicated 15 kV test leads which are double insulated with clips designed for 15 kV creepage paths. The 15 kV leads are supplied in a rucksack. Suitably rated HV gloves and other personal protection equipment are required to be worn when testing.

The MIT range share dual case design which includes a tough outer case to protect the tester from knocks/drops and an inner fire retardant case. The IP rating is IP 65 case closed eliminating moisture and dust ingress.

An intuitive user interface ensures no lost time remembering how to use the tester. Simplicity of operation is achieved with two rotary switches and the large backlight display which enables multiple results to be displayed simultaneously. A graphical quick start guide is provided inside the lid to assist first time users.

Five preset voltage ranges are provided in insulation test mode, plus a user settable lock voltage range. Preconfigured diagnostic tests include Polarisation Index (PI), Dielectric Absorption Ratio (DAR), dielectric discharge (DD), Stepped Voltage (SV) and ramp test.

Advanced memory storage includes time/date stamping of results, logging of data and recall of results to screen. A fully isolated USB interface is used for safe transfer of data to Megger's asset management software; PowerDB Pro, Advanced and Lite packages.

Test leads are double insulated  $\square$  with clamps rated at 3 kV  $\square$  equivalent to 6 kV single insulation for the medium clip leadset and 5 kV  $\square$  equivalent to 10 kV single insulation for the large clip. The 15kV leadset is insulated to 15kV.

### FEATURES AND BENEFITS

- Insulation resistance up to 30 TΩ @ 15 kV, 20 TΩ @ 10kV, 10 TΩ @ 5 kV
- IR, Timed IR, DAR, PI, DD, SV and ramp diagnostic tests
- High current – 3 mA short circuit current
- High noise immunity – 3mA (5kV and 10kV) 6mA (15kV) of noise rejection
- Li-ion battery – up to 6 hrs continuous testing @ 5 kV with a 100M load, battery meets IEC 62133
- Safety rating: CATIV 600 V to 3000 m (5 kV, 10 kV)  
CATIV 1000 V to 3000 m (15 kV)
- Large LCD display with backlight
- Dedicated voltmeter function (30 V to 660 V)
- Advanced memory, on screen recall and real time clock for date/time stamped results
- Download of on-board results via USB interface
- PowerDB Lite asset management software
- Recorded temperature (measured by independent instruments) can be saved with test result
- PowerDB Lite asset management software supplied

### APPLICATION

The Insulation Resistance (IR) test is a quantitative test which indicates the effectiveness of a product's electrical insulation. Applications include cables, transformers, motors/generators, circuit breakers and bushings. Common insulation tests are the "spot test", a 1 minute IR test and a 10 minute Polarisation Index (PI) test, where PI is the ratio  $R_{10min}/R_{1min}$  and temperature independent.

### ELECTRICAL SPECIFICATIONS

#### AC Voltage input range:

**5 kV, 10 kV:** 90-264 V rms, 47- 63 Hz 100VA

**15 kV:** 90-264 V rms, 47- 63 Hz 200VA

**Battery:** 11.1 V, 5.2Ah Li-ion batteries, meet IEC 62133:2003, MIT1525 has 2 battery packs

**Battery life MIT515, MIT525:** 6 hours (typical) continuous testing at 5 kV with a 100 MΩ load

**Battery life MIT1025:** 4.5 hours (typical) continuous testing at 10kV with a 100 MΩ load

**Battery life MIT1525:** 4.5 hours (typical) continuous testing at 15 kV with a 100 MΩ load

**Battery charge time:** 2.5 hours from deep discharge, 2 hours normal discharge

**Test voltages MIT515, MIT525:** 250 V, 500 V, 1000 V, 2500 V, 5000 V, V<sub>⊕</sub>

**Test voltages MIT1025:** 500 V, 1000 V, 2500 V, 5000 V, 10000 V, V<sub>⊕</sub>

**Test Voltages MIT1525:** 1000 V, 2500 V, 5000 V, 10000 V, 15000 V, V<sub>⊕</sub>

**Lock test voltage V<sub>⊕</sub>:** 40 V to 1 kV in 10 V steps, 1 kV to 5 kV in 25 V steps, 5 kV to 15 kV in 25 V steps

**Voltage o/p accuracy:** +4%, -0%, ±10 V nominal test voltage at 1GΩ load (0°C to 0°C)

**Resistance Range:**  
10 k to 10 TΩ @ 5 kV  
20 k to 20 TΩ @ 10 kV  
10 k to 30 TΩ @ 15 kV

#### Accuracy from 1 MΩ to:

#### MIT515, MIT525 accuracy (23 °C)

	5000 V	2500 V	1000 V	500 V	250 V
±5% to	1 TΩ	500 GΩ	200 GΩ	100 GΩ	50 GΩ
±20% to	10 TΩ	5 TΩ	2 TΩ	1 TΩ	500 GΩ

#### MIT1025 accuracy (23 °C)

	10 kV	5000 V	2500 V	1000 V	500 V
±5% to	2 TΩ	1 TΩ	500 GΩ	200 GΩ	100 GΩ
±20% to	20 TΩ	10 TΩ	5 TΩ	2 TΩ	1 TΩ

#### MIT1525 accuracy (23 °C)

	15 kV	10 kV	5000 V	2500 V	1000 V
±5% to	3 TΩ	2 TΩ	1 TΩ	500 GΩ	200 GΩ
±20% to	30 TΩ	20 TΩ	10 TΩ	5 TΩ	2 TΩ

**Centrally positioned Guard ring:** Guard parallel leakage, resistance down to 250 kΩ with a maximum additional resistance error of 1% with a 100 MΩ load.  
100 kΩ to 10 TΩ

**Display range analogue:**

**Display range digital:**

**Short circuit current:**

**Insulation alarm:**

**Capacitor charge:**

**Capacitor discharge:**

**Capacitance range:**

(> 500 V)

**Capacitance accuracy:**

(23 °C)

**Current measurement range:**

**Current measurement accuracy:**

**Interference (noise) rejection:**

**MIT515, MIT525,**

**MIT1025**

**MIT1525**

**Voltmeter range:**

**Voltmeter accuracy:**

**Timer range:**

**Memory capacity:**

**Test regimes:**

**Interface:**

**Real time output:**

### ENVIRONMENTAL SPECIFICATIONS

**Altitude:** 3000 m (5 kV, 10 kV)

3000 m (15 kV)

**Operating temperature:**

**Storage temperature:**

**Humidity:**

**Ingress protection:**

3000 m (5 kV, 10 kV)

3000 m (15 kV)

-20 °C to 50 °C

-25 °C to 65 °C

90% RH non-condensing at 40 °C

IP65 (lid closed), IP40 (lid open)

## SAFETY SPECIFICATIONS

**Safety:** CATIV 600 V to 3000 m (5 kV, 10 kV)  
CATIV 1000 V to 3000 m (15 kV)  
Meets the requirements of IEC 61010-1,

**EMC:** Meets the requirements of IEC61326-1

### Dimensions:

**MIT515, MIT525, MIT1025** L 315 mm x W 285 mm x H 181 mm  
**MIT1525** L 360 mm x W 305 mm x H 194 mm

### Weight:

**MIT515, MIT525, MIT1025** 4.5 kg  
**MIT1525** 6.5 kg

## ORDERING INFORMATION

Item (Qty)	Order Code	Item (Qty)	Order Code
MIT515-UK	1001-935	<b>HV test lead sets 5kV, 10kV</b>	
MIT515-US	1001-936	5 m leadset x 3, large insulated clips*	1002-645
MIT515-EU	1001-937	8 m leadset x 3, large insulated clips	1002-646
MIT515-AU	1001-938	10 m leadset x 3, large insulated clips	1002-647
MIT525-UK	1001-939	15 m leadset x 3, large insulated clips	1002-648
MIT525-US	1001-940	5 m leadset x 3, medium insulated clips*	1002-641
MIT525-EU	1001-941	8 m leadset x 3, medium insulated clips	1002-642
MIT525-AU	1001-942	10 m leadset x 3, medium insulated clips	1002-643
MIT1025-UK	1001-943	15 m leadset x 3, medium insulated clips	1002-644
MIT1025-US	1001-944	3 m leadset x 3, bare compact clips	8101-181
MIT1025-EU	1001-945	8 m leadset x 3, bare compact clips	8101-182
MIT1025-AU	1001-946	15 m leadset x 3, compact bare clips	8101-183
MIT1525-UK	1002-907		
MIT1525-US	1002-909	<i>* These test leads may also be supplied in non-standard lengths to suit a particular application / requirement. Please contact Megger for a quotation, minimum order quantities may apply.</i>	
MIT1525-EU	1002-908		
MIT1525-AU	1002-910		
<b>Included Accessories</b>		<b>Screened HV test lead sets</b>	
Power lead		3 m, 5 kV screened un-insulated small clips	6220-835
USB cable		15 m, 5 kV screened un-insulated small clips	6311-080
PowerDB Lite software		3 m, 10 kV screened un-insulated small clips	6220-834
Product Information CD		10 m, 10 kV screened un-insulated small clips	6220-861
<b>Included Accessories 5 kV, 10 kV, 15kV</b>		15 m, 10 kV screened un-insulated small clips	6220-833
3 m leadset x 3, medium insulated clips	1002-531		
3 m leadset x 3, large insulated clips (MIT1025 only)	1002-534	<b>Other</b>	
3m leadset x 3, large 15 kV insulated clips (MIT1525 only)	1002-949	CB101, 5 kV Calibration Box	6311-077
<b>Optional Accessories</b>		Calibration Certificate - CB101	1000-113
<b>1 kV test lead sets</b>		UKAS calibration Certificate CB101	1000-047
Fused test probe and clip lead set	1002-913		
Control circuit test lead set	6220-822		

**Group exporter:**  
**Multi-Tek International**  
email: [mti@multitekintl.com](mailto:mti@multitekintl.com)

**CERTIFICATION ISO**  
Registered to ISO 9001:2008 Cert. no. Q 09250  
Registered to ISO 14001:2004 Cert. no. EMS 61597

**MIT515-525-1025-1525\_DS\_en\_V01**

Megger is a registered trademark